

FEATURES

- The most versatile LED tube on the market. Installation methods include single end bypass, dual end bypass and type A ballast compatibility. 10K Surge protection with premium flyback driver technology allows for up to 68,000 hours of operational life.
- 120°-155° wide beam angle / Frosted & Clear Lens
- Socket: Bi-Pin
- LED Type: SMD2835

- CRI >85
- CRT: 2700K - 6000K
- Material: PC Cover / Aluminum

- Warranty: up to 10 years
- Operational Hours: 68,000 Hours

APPLICATIONS

- Schools, offices, hospitals, supermarkets, retails, and factories.

PRODUCT DIMENSION

Product Length	Total Length (mm)	Cap-Base
4FT	1198 x 26mm	Bi-Pin



ELECTRICAL SPECIFICATIONS

- Driver Type: Built-in, ballast compatible
- Input Voltage: AC100-277V
- Frequency: 50/60Hz
- Power Factor: >0.9

CERTIFICATION

- Certification: UL, DLC, RoHS, Fcc

APPLICATION

- Application: Indoor use
- Environment: -20°C~40°C/10%~90%RH

PACKING

- Package: 25pcs/carton
- Gross Weight: 6.5 kg/carton
- Package Size: 1270 x 210 x 210mm



T8 LED TUBE - NORMAL EFFICIENCY


Item	Wattage	Cap-Base	CCT	Light Output	Efficiency	LED Type	Product Size	Main Material	Beam Angle	Certificate
US4T812WGO-3K	12W	G13 [G13 Medium Bi-Pin]	3000K	1683.28lm	138.2 lm/w	SMD2835	1198 x 26mm	Aluminum and PC Cover	120°-155°	UL, DLC
US4T812WGO-4K			4000K	1895.08lm	151.6 lm/w					
US4T812WGO-5K			5000K	2006.74lm	165.3 lm/w					

Item	Wattage	Cap-Base	CCT	Light Output	Efficiency	LED Type	Product Size	Main Material	Beam Angle	Certificate
US4T815WGO-3K	15W	G13 [G13 Medium Bi-Pin]	3000K	2041.88lm	134.6 lm/w	SMD2835	1198 x 26mm	Aluminum and PC Cover	120°-155°	UL, DLC
US4T815WGO-4K			4000K	2129.75lm	140.3 lm/w					
US4T815WGO-5K			5000K	2162.86lm	142.2 lm/w					


Item	Wattage	Cap-Base	CCT	Light Output	Efficiency	LED Type	Product Size	Main Material	Beam Angle	Certificate
US4T818WGO-3K	18W	G13 [G13 Medium Bi-Pin]	3000K	2452.98lm	135.3 lm/w	SMD2835	1198 x 26mm	Aluminum and PC Cover	120°-155°	UL, DLC
US4T818WGO-4K			4000K	2590.01lm	142.7 lm/w					
US4T818WGO-5K			5000K	2673.93lm	147 lm/w					

INSTALLATION GUIDE

1. Compatible with Magnetic ballast



2. Compatible with electronic ballast



3. One side power without ballast



4. Two side power without ballast



PACKAGE

	Dimensions	pcs/ctn
Carton	49"x8.3"x9.5" inch	30 pcs

