

SPECIFICATIONS AND FEATURES

Stadium Flood Light

Product Type	DLC Approved Stadium Flood Light
Manufacturer	uSaveLED
Model Number.....	USFL100WGL-DLC
Special Price (10 units or more*).....	\$529.00
Price (less than 10 units*)	\$559.00
Voltage...90-305VAC/180-528VAC Available (Add \$20.00)/ 12VDC Available	
Wattage	100
Lumens	15,000
Lumens Per Watt	150
LED Chipset	CREE
Beam Angle (degrees)	10/24/38/60/90/120
Kelvin (CCT).....	3000/4000/5000/5700/6500
CRI	>80 / >90 Available for 3000K, 4000K, or 5000K (Add \$10.00)
Power Factor.....	>0.98
Life Span (Hours)	80,000+
Dimming Options	Non-Dimmable Standard / 0-10V Dimming Available (Add \$59.00) / Dali Dimming Available (Add \$59.00) / DMX Dimming Available (Add \$139.00)
Waterproof	YES (IP67)
Certifications.....	DLC, ETL, CE, RoHS, UL Driver
EPA Rating	1.23Ft ²
Impact and Vibration Resistance (IK Rating)	IK10
Length of Warranty (YEARS).....	5
Operating Temperature	-40° to +65°C (-40° to +149°F)
Dimensions	14.97" x 11.82" x 3.94"
Weight.....	13.23 lbs
Suggested Replacement For:	400W Metal Halide
Percent of wattage saved from	75% average replacement*

(*excludes savings in labor, frequency of bulb changes, ballast, and HVAC savings)



Design Lights Consortium (DLC) approved for rebates in many municipalities. These high lumen powerhouses are low power equivalents to traditional HID floodlights. Featuring the largest cooling area and best heat dissipation on the market, these flood lights last over 80,000 hours compared to less than 10,000 hours for a HID bulb. Zero Flickering light is perfect for slow motion images and HDTV live broadcasting. Provides excellent security, warehouse, architectural, landscape, stadium, playground and all around outdoor lighting. These flood lights are waterproof and use 70% less electricity. Uses UL rated IP67 Meanwell Driver.

