

## Features

- \* Customized **USA CREE** LED, 150lm/w, CRI **Ra80-93**. Junction temperature **<70°C**
- \* TaiWan **MeanWell** LED Drivers, wide AC90V~305V, **PF>0.98**, low THD<9%
- \* Ultra-low luminous decay **<5%** in 5 years. L70>50,000hrs. Design lifespan **80,000hrs**
- \* **SONY 4D** active heat dissipation technology. Unitized module design, **biggest cooling area**
- \* Constant current and constant voltage design, much more reliable than other LED floodlights
- \* Japan **calculus optical DIWL lens**, light transmittance of PMMA up to 98%.
- \* **10°24°38°60°90°** beam angles and excellent uniformity
- \* High strength structure coated with corrosion resistant polyester powder, real **anti-corrosion**
- \* Excellent optical design, low UGR. **Noflickering** for slow-motion image. Applicable to **HDTV live broadcasting**
- \* Intelligent dimming system. 0-10V, **1-10V**, Triac and **DALI** dimming models are available
- \* **CE(TUV) RoHS ETL FCC DLC** and **IP67** approved, **5 years warranty**
- \* Widely used in stadium, sports field, tunnel, high mast lighting, light tower, ports... Applicable for most places



**Product Certification:** CE\RoHS\ TUV\GS\SAA\C-Tick\ETL\FCC\DLC\IP67

## Driver:



## Driver certification:



Safety and EMC design refer to EN60598-1, subject 8750(UL), CNS15233, GB7000.1, FCC part18.

SAFETY & EMC	SAFETY STANDARDS	Note.7	UL1012, CAN/CSA-C22.2 No. 107.1-01, UL8750, CSAC22.2 No. 250.0-08, TUV EN61347-1, EN61347-2-13 independent (except for HLG-240H C type), UL60950-1, UL8750, TUV EN60950-1, IP65 or IP67, J61347-1, J61347-2-13 approved
	WITHSTAND VOLTAGE		I/P-O/P:3.75KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC
	ISOLATION RESISTANCE		I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C/ 70% RH
	EMC EMISSION		Compliance to EN55015, EN55022 (CISPR22) Class B, EN61000-3-2 Class C ( $\geq 50\%$ load) ; EN61000-3-3
	EMC IMMUNITY		Compliance to EN61000-4-2,3,4,5,6,8,11, EN61547, EN55024, light industry level (surge 4KV), criteria A


## LED Chip:




## LED COMPONENTS IES LM-80 TESTING RESULTS

Data Set	Case Temp. [T <sub>s</sub> ]	Ambient Temp. [T <sub>A</sub> ]	Drive Current [I <sub>r</sub> ]	Average Lumen Maintenance at 6,000 hours	Average Chromaticity Shift ( $\Delta u'v'$ ) at 6,000 hours	Reported TM-21 Lifetimes
3+	105°C	105°C	200 mA (37V) 400 mA (18V)	98.4% 60000hours=84%	0.0008	L90(10k) > 60,500 hrs L80(10k) > 60,500 hrs L70(10k) > 60,500 hrs
4+	55°C	55°C	375 mA (37V) 750 mA (18V)	97.7%	0.0006	L90(10k) > 60,500 hrs L80(10k) > 60,500 hrs L70(10k) > 60,500 hrs
5+	85°C	85°C	375 mA (37V) 750 mA (18V)	97.6%	0.0007	L90(9k) > 54,400 hrs L80(9k) > 54,400 hrs L70(9k) > 54,400 hrs


## Material:



Aluminium alloy heatsink  
With electrophoresis treatment




Aluminium alloy housing  
With electrostatic spraying




Stainless steel SUS304  
Fixed Handle  
With electrophoresis treatment

## Heat Dissipation Structure:

The heat radiator area of the LED floodlight is the biggest in the high-power LED industry at present



Driver inside with ventilation design, protect it from the damage of sunshine



# Specification

## Main Parameters:

Input Voltage	90-305VAC/480V, 50/60 Hz
INRUSH CURRENT(Typ)	COLD START 75A(twidth=570μs measured at 50%Ipeak)at 230VAC
LEAKAGE CURRENT	<0.75mA/277VAC
POWER FACTOR(Typ.)	PF>0.98/115VAC, PF>0.95/230VAC at full lead
LED Light Source	CREE Xlamp
LED Qty	24PCS
LED Power	200W
Total System Power	215W
Power supply	TaiWan MeanWell
Driver Qty	1PCS
LED Luminous Efficiency	150lm/W
LED Initial Luminous Flux	30000Lm
Illuminance Uniformity	>0.8
Color Temperature	2700K,3000K,3500K,4000K,5000K,5700K,6500K
Color Rendering Index	80+ / 90+
Light Distribution	Asymmetric / Rectangular
Beam Angle	10°/24°/38°/60°/90°/120°
LED Junction Temperature	≤70℃ (@ Ta=25℃)
Working Temperature	-40℃ ~ +65℃
Storage Temperature	-40℃ ~ +65℃ (Best 25℃)
IP Rating	IP67
Net weight	10Kg
Life-span	>80,000H
Shell Color	Black/Silver/Grey

**Luminaire:**

Report No: N/A

Test No: N/A

LampCAT:

Lamp flux(lm): 1236.2

Number of Lamps: 24

Length(mm): 380

Phm Type: C

Voltage(V): 120.15

Current(A): 1.6646

Power (W): 198.8300

PF: 0.9941

Ballast type:

Width(mm): 210

Height(mm): 21

**Photometric Results**


Lumens(lm): 29669.04

Efficiency(%): 100.00%


Lumens(lm)/Power(W): 149.22

Central intensity(cd): 33807.850



Maximum intensity(cd): 34219.530



Max , Ave      Beam angle of C180plane55.80




## Beam Angle



Multi Angle Applications



## Two Angle Showing






# Wiring Diagram


- Black—Neutral
- White—Line
- Green—Ground



Triphase Cable





A  
B  
C  
N  
GND




## Installation Instructions

Through the screw, choose and adjust the angle of the bracket you need before installaing



## Applications




Applied in large sports field lighting, football, basketball, golf and tennis court, racetrack, badminton, roads, high-rise buildings, tower lights, etc. Can also be applied in large square, airport, commercial building, construction engineering, farm, amusement parks, parking lots, harbor, industrial buildings, and other special lighting environment.



## Maintenance / Repairing Instructions:

1. Make sure the power has been turned off before maintenance or repairing.
2. Clean the LED Lens regularly to maintain high transmission of light.
3. Clean up the dust from the lens and heat sink regularly to keep sound heat dispersion.
4. Be careful not to use corrosive solution for cleaning, preferably with a wet cloth.
5. When install or replace power supply, directly open the back cover with a screwdriver, then remove the power supply. On DC power output, the red cable corresponds to the positive power polarity, and black corresponds to the negative.  
Pay attention do not reverse the positive and the negative in any circumstance.

## Product Dimension-(mm)



Free-inspection Export Wooden Packing



Packing Size(L*W*H) /1unit	610*510*210mm
N.W.	10.0Kg
G.W.	16.0Kg