

SPECIFICATIONS AND FEATURES

Stadium Flood Light

Product Type Heavy Duty Round Stadium Flood Light
 Manufacturer uSaveLED
 Model Number..... USFLHDR700WBR
 Special Price (10 units or more*).....\$1,839.00
 Price (less than 10 units*)\$2,029.00
 Voltage 100-277VAC Standard /
 347-480VAC Available (Add \$89.00)
 Wattage 700
 Lumens 105,000 @ 15° / 112,000 @ 30°
 Lumens Per Watt 120lm/W @ 15° / 160lm/W @ 30°
 LED Chipset Philips Lumileds 5050
 Mounting.....Double Jointed U-Bracket Standard / Knuckle
 Flat Bracket Available (Add \$49.00)
 EPA Rating3.12Ft²
 Beam Angle (degrees)..... 15°/30°
 Kelvin (CCT).....3000/4000/5000/5700
 CRI >70
 Life Span (Hours)50,000+
 Dimmable.....Dali Dimming Driver Available (Add \$16.00)
 Waterproof YES (IP65)
 IK Rating (Impact and Vibration Resistance)IK10
 Certifications..... ETL, CE, RoHS
 Length of Warranty (YEARS).....5
 Dimensions ..28.87"x8.98" (Mounting Options May Change
 Dimensions)
 Weight..... 67.3 lbs
 Suggested Replacement For: 3200W Metal Halide
 Percent of wattage saved from 78.13%
 average replacement*
 (*excludes savings in labor, frequency of bulb changes, ballast, and HVAC
 savings)
 Additional Options Dark Sky Shield Available (Add \$55.00)
 / Aiming Laser Available (Add \$49.00)



ETL Rated for Top Quality. Zero Flickering light is perfect for slow motion images and HDTV live broadcasting. Provides excellent security, warehouse, architectural, landscape, stadium, playground and all around outdoor lighting.

