

SPECIFICATIONS AND FEATURES

Stadium Flood Light

Product Type DLC Approved Stadium Flood Light
 Manufacturer uSaveLED
 Model Number USFLR300WBR
 Special Price (10 units or more*) \$1,029.00
 Price (less than 10 units*) \$1,139.00
 Voltage 100-277VAC Standard /
 347-480VAC Available (Add \$65.00)
 Wattage 300
 Lumens 33,000-48,000
 Lumens Per Watt 110-160
 LED Chipset CREE / Philips Lumileds
 Mounting Double Jointed U-Bracket Standard /
 Knuckle Slip Fitter Available (Add \$35.00)
 EPA Rating 1.36Ft²
 Beam Angle (degrees) 10°/30°/90°/120°
 Kelvin (CCT) 3000/4000/5000/5700
 CRI >80 / >90 CRI Available (Add \$5.00)
 Power Factor >0.9
 Life Span (Hours) 50,000+
 Dimmable I-10V Dimming Available (Add \$19.00) / Dali
 Dimming Available (Add \$19.00) / Wifi Controlled Zigbee
 Dimming System Available (Pricing Based on Project)
 Waterproof YES (IP65)
 Certifications DLC, UL, CE, RoHS
 Length of Warranty (YEARS) 5
 Dimensions 18.11"x4.15" (Mounting Options May
 Change Dimensions)
 Weight 41.89 lbs
 Suggested Replacement For: 1200W Metal Halide
 Percent of wattage saved from 75%
 average replacement*
 (*excludes savings in labor, frequency of bulb changes, ballast, and HVAC
 savings)
 Additional Options Dark Sky Shield Available (Add \$69.00)
 / Aiming Laser Available (Add \$49.00)



Design Lights Consortium (DLC) approved for rebates in many municipalities. UL Rated for Top Quality. Zero Flickering light is perfect for slow motion images and HDTV live broadcasting. Provides excellent security, warehouse, architectural, landscape, stadium, playground and all around outdoor lighting.

