



The K5 Series



XL750 LED Grow Light:

uSaveLED Model Number: USGL430WKND

Dimensions: 23" x 17" x 3.5"

Weight: 28 lbs. Actual Wattage: 430w

HID Wattage Equivalent: 750w

Total Diodes: 208

Diode Wattage: Perfect Mix of 3 Watt & 5 Watt

Footprint: 4' x 4'

Input Voltage: 100-240V AC Power Input Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment Output Voltage: UL Standard Output Voltage - Less than 76V DC Amperage: 3.58 at 110 Volts



XL1000 LED Grow Light:

uSaveLED Model Number: USGL650WKND

Dimensions: 26" x 20"x 3.5"

Weight: 36 lbs.

Actual Wattage: 650 Watts

HID Wattage Equivalent: 1000 Watts

Total Diodes: 320

Diode Wattage: Perfect mix of 3 Watt & 5 Watt

Footprint: 5' x 5'

Input Voltage: 100-277 Volts AC Power input Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment

Output Voltage: UL Standard Output Voltage - Less than 76 Volts DC Amperage: 5.25 at 110 Volts

The K3 Series



L300 LED Grow Light:

uSaveLED Model Number: USGL220WKND

Dimensions: 15" x 11" x 3"

Weight: 13 lbs. Actual Wattage: 220w

HID Wattage Equivalent: 300w

Total Diodes: 90 Diode Wattage: 3 Watt Footprint: 2' x 3'

Input Voltage: 100-240V AC Power Input Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment

Output Voltage: UL Standard Output

Voltage - Less than 76V DC Amperage: 1.83 at 110 Volts



L450 LED Grow Light:

uSaveLED Model Number: USGL270WKND

Dimensions: 20" x 11" x 3"

Weight: 16 lbs. Actual Wattage: 270w

HID Wattage Equivalent: 450w

Total Diodes: 120 Diode Wattage: 3 Watt Footprint: 2.5' x 3.5'

Input Voltage: 100-240V AC Power Input Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment

Output Voltage: UL Standard Output

Voltage - Less than 76V DC Amperage: 2.25 at 110 Volts



L600 LED Grow Light:

uSaveLED Model Number: USGL320WKND

Dimensions: 25" x 11" x 3"

Weight: 20 lbs. Actual Wattage: 320w

HID Wattage Equivalent: 600w

Total Diodes: 150 Diode Wattage: 3 Watt Footprint: 3' x 4'

Input Voltage: 100-240V AC Power Input Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment

Output Voltage: UL Standard Output

Voltage - Less than 76V DC Amperage: 2.67 at 110 Volts





uSaveLED Model Number: USVEG320WKND Footprint: 3' x 4'

Dimensions: 25" x 11" x 3"

Weight: 20 lbs.

Actual Wattage: 320w HID Wattage Equivalent: 600w

Total Diodes: 150 Diode Wattage: 3 Watt

Input Voltage: 100-240V AC Power Input

Work Frequency: 50/60 Hz - Suitable for

Global Energy Environment Output Voltage: UL Standard Output Voltage - Less than 76V DC Amperage: 2.67 at 110 Volts