




USHIBAYSxxxWHS

LED Low Profile Linear High Bay



USHIBAYS50WHS



H:95mm

L:305mm

W:122mm

All Dimensions are in[mm]

Electro-Optical Characteristics

Features

Input Voltage(typ)	AC90-305V/180-528V
Tested@(Voltage)	220Vac
Power Consumption	50w
Current Consumption	0.23A
Efficacy:(Lm/w)	170
Lumens	8500lm
THD	15%-20%
Power Factor	0.95
CRI(Ra)	80
CCT	2700-6000k
Viewing Angle	60/90/120°
LED source	PHILIPS 3030Leds

OperatingTemperature	-40°Cto+55°C
Dimmable	YES (0-10V)
Housing Material	aviation aluminum
Lens Material	PC
Housing Color	White/Black
Driver	MEANWELL
Protection Rating	IP66
Warranty	7Years
SMD LED/Qty.	77pcs
Net weight	2.7kg
Outer carton size(cm)	39.5*19.5*17cm
G.W per ctn	3.7kg

--	--	--	--	--	--

USHIBAYS100WHS



H:95mm
W:122mm

L:600mm



All Dimensions are in[mm]

Electro-Optical Characteristics

Features

Input Voltage(typ)	AC90-305V/100-277V/180-528V
Tested@(Voltage)	220Vac
Power Consumption	100w
Current Consumption	0.45A
Efficacy:(Lm/w)	170
Lumens	17000lm
THD	15%-20%
Power Factor	0.95
CRI(Ra)	80
CCT	2700-6000k
Viewing Angle	60/90/120°
LED source	PHILIPS 3030Leds

OperatingTemperature	-40°C to +55°C
Dimmable	YES (0-10V)
Housing Material	Aviation aluminum
Lens Material	PC
Housing Color	White/Black
Driver	MEANWELL
Protection Rating	IP66
Warranty	7Years
SMD LED/Qty.	154pcs
Net weight	3.6kg
Outer carton size(cm)	69.5*19.5*17cm
G.W per ctn	4.7kg

--	--	--	--	--	--

USHIBAYS150WHS



L:895mm

W:122mm

H:95mm



All Dimensions are in[mm]

Electro-Optical Characteristics


Features

Input Voltage(typ)	AC90-305V/100-277V/180-528V
Tested@(Voltage)	220Vac
Power Consumption	150w
Current Consumption	0.68A
Efficacy:(Lm/w)	170
Lumens	25500lm
THD	15%-20%
Power Factor	0.95
CRI(Ra)	80
CCT	2700-6000k
Viewing Angle	60/90/120°
LED source	PHILIPS 3030Leds

OperatingTemperature	-40°Cto+55°C
Dimmable	YES (0-10V)
Housing Material	aviation aluminum
Lens Material	PC
Housing Color	White/Black
Driver	MEANWELL
Protection Rating	IP66
Warranty	7Years
SMD LED/Qty.	231pcs
Net weight	5.6kg
Outer carton size(cm)	98.5*19.5*17cm
G.W per ctn	6.7kg

--	--	--	--	--	--

USHIBAYS200WHS / USHIBAYS250WHS



L:1190mm

W:122mm

H:95mm



All Dimensions are in[mm]

Electro-Optical Characteristics

Features






Input Voltage(typ)	AC90-305V/100-277V/180-528V
Tested@(Voltage)	220Vac
Power Consumption	200w/250w
Current Consumption	0.91A/1.145A
Efficacy:(Lm/w)	170
Lumens	34000lm/42500lm
THD	15%-20%
Power Factor	0.95
CRI(Ra)	80
CCT	2700-6000k
Viewing Angle	60/90/120°
LED source	PHILIPS 3030Leds

OperatingTemperature	-40°Cto+55°C
Dimmable	YES (0-10V)
Housing Material	aviation aluminum
Lens Material	PC
Housing Color	White/Black
Driver	MEANWELL (ELG-240)
Protection Rating	IP66
Warranty	7Years
SMD LED/Qty.	308pcs
Net weight	6.9kg
Outer carton size(cm)	128*19.5*17cm
G.W per ctn	8.2kg

--	--	--	--	--	--



Installation accessories for choosing

	HS-01	A, Standard fittings with 2pcs buckles,if need other installation way, the price for accessories are as follows
	HS-02	A, Suspended Mounting B, Chain length : 1m/pcs, total 2 pcs with safty ring and screws.
	HS-03	A, 2pcs Pole-hang buckle with screws
	HS-04	A, 1 Connection buckle(For Two or more modules) with screws
	HS-05	A, Adjust bracked : 1、 Surfaced mounting ; 2、 wall mounted ; 3、 ground mounted ; B, Can adjusted different beam angle. Maximum 90°. C, 1 brackets with screws