

SPECIFICATIONS AND FEATURES

Parking / Street Light

Product Type..... Tool-Free LED Roadway Light
 Manufacturer uSaveLED
 Model Number..... USSLC100WPL
 Price..... \$345.95
 Voltage 100-277VAC Standard /
 347-480VAC Available (Add \$79.00)
 Wattage..... 100
 Lumens 13,000
 Lumens Per Watt 130
 Kelvin (CCT)..... 2700 / 3000 / 4000 / 5000
 Beam Angle..... Type 2 Distribution Lens Standard
 / Type 3 Distribution Lens Available (Add \$15.00) / Type 4
 Distribution Lens Available (Add \$15.00)
 Mounting Fits Most
 Standard Roadway Upsweep Arms, 4-Bolt Mount Bracket
 Supplied Fits 1" to 2 3/8" OD Pipe Arms.
 CRI >70
 Power Factor..... >0.9
 Life Span (Hours) 100,000+
 Dimmable..... YES (0-10V)
 Waterproof YES (IP66)
 Certifications..... UL, RoHS
 Length of Warranty (YEARS)..... 5yr
 Operating Temperature +4° to +45°C (20° to +113°F)
 Dimensions 23.63"x11.23"x5.60"
 Suggested Replacement For: 400W Metal Halide
 Percent of wattage saved from75%
 average replacement*
 (*excludes savings in labor, frequency of bulb changes, ballast, and HVAC
 savings)
 Sensors..... 120-277VAC Twist Lock
 Photocell Available (Add \$49.00) / 120-277VAC Daylight
 Harvesting Twist Lock Photocell Available (Add \$109.00)
 / 480VAC Twist Lock Photocell Available (Add \$49.00) /
 Motion Sensor Available (Add \$119.00)
 Notes..... ANSI C136.41 7-Pin
 Receptacle and Shorting Cap Included (Compatible with
 3-Prong Photocell and Many IoT Node Control Devices) /
 6KA Surge Protection in Driver / 10KA Additional Surge
 Protection Device Included



Quick Ship Item! \UL Rated for Top Quality. Featuring a Sleek Selfr Clean Modern Design with Low EPA and No Visible Heat Sink. Inter-net of Things (IoT) Ready. These fixture are perfect for streets, pathways, sidewalks, road-ways, neighborhoods, and much more!

