

SPECIFICATIONS AND FEATURES

Parking / Street Light

Product Type..... Tool-Free LED Roadway Light
 Manufacturer uSaveLED
 Model Number..... USSLC150WPL
 Price..... \$385.95
 Voltage 100-277VAC Standard / 347-480VAC Available (Add \$79.00)
 Wattage..... 150
 Lumens 17,550
 Lumens Per Watt 117
 Kelvin (CCT)..... 2700 / 3000 / 4000 / 5000
 Beam Angle..... Type 2 Distribution Lens Standard / Type 3 Distribution Lens Available (Add \$15.00) / Type 4 Distribution Lens Available (Add \$15.00)
 Mounting Fits Most Standard Roadway Upsweep Arms, 4-Bolt Mount Bracket Supplied Fits 1" to 2 3/8" OD Pipe Arms.
 CRI >70
 Power Factor..... >0.9
 Life Span (Hours) 100,000+
 Dimmable..... YES (0-10V)
 Waterproof YES (IP66)
 Certifications..... UL, RoHS
 Length of Warranty (YEARS)..... 5yr
 Operating Temperature +4° to +45°C (20° to +113°F)
 Dimensions 23.63"x11.23"x5.60"
 Suggested Replacement For: 600W Metal Halide
 Percent of wattage saved from 75% average replacement*
 (*excludes savings in labor, frequency of bulb changes, ballast, and HVAC savings)
 Sensors..... 120-277VAC Twist Lock Photocell Available (Add \$49.00) / 120-277VAC Daylight Harvesting Twist Lock Photocell Available (Add \$109.00) / 480VAC Twist Lock Photocell Available (Add \$49.00) / Motion Sensor Available (Add \$119.00)
 Notes..... ANSI C136.41 7-Pin Receptacle and Shorting Cap Included (Compatible with 3-Prong Photocell and Many IoT Node Control Devices) / 6KA Surge Protection in Driver / 10KA Additional Surge Protection Device Included



Quick Ship Item! \UL Rated for Top Quality. Featuring a Sleek Selfr Clean Modern Design with Low EPA and No Visible Heat Sink. Inter-net of Things (IoT) Ready. These fixture are perfect for streets, pathways, sidewalks, roadways, neighborhoods, and much more!

